

Slide Compound Miter Saw

LS1019L

1 510 W • 260 mm • 3 200 min⁻¹

Efficient and accurate saw with a laser for high-capacity applications

An accurate high-capacity saw with a 1 510 W motor for building and other worksites. The dual slide system reduces the need for space, enabling the machine to be placed by a wall. The bevel lock is located at the front of the saw. Excellent dust removal function.



DXT
Deep and Exact Cutting Technology

Technical specifications

Capacity 90°	91 x 279 / 68 x 310 mm
Continuous Input Power No load speed	1510 W 3200 min ⁻¹
Capacity 45°	91 x 197 / 68 x 218 mm
Capacity 45° left	58 x 279 / 42 x 310 mm
Bevel capacity right 45°	43 x 279 / 29 x 305 mm
Max. Bevel Range (Left)	48 / 48 °
Max. Mitre Range (Left)	60 / 60 °
Blade Diameter	260 mm
Bore Size (Arbor Diameter)	30 mm
Power Supply Cord	2,5 m
Sound Power Level (L _{WA})	101 dB(A)
Sound Pressure Level (L _{pA})	91 dB(A)

User benefits

- Outstanding dust extraction
- Can be placed all the way to the wall due to new construction
- Superior capacity

EAN 0088381843997

Link to product - www.makita.com



Related products

Optional AC

122470-4

Horizontal Vice Assembly



122852-0

Dust bag



192669-5

Crown Molding Stopper Set



195253-5

Crown molding stopper set



762001-3

Triangular Rule



781044-6

Hex Wrench 6



783208-8

Hex Wrench 2,5 mm



B-29496

Circular saw blade, Specialized T.C.T,



B-32487

Circular Saw Blade, MakBlade Plus,



B-32873

Circular Saw Blade, Makblade T.C.T,



B-64630

Circular Saw Blade, Efficut, TCT,



B-67284

Circular Saw Blade, Efficut, T.C.T,



E-07705

T.C.T. Saw Blade 260 x 30 mm, 24 T,



E-12201

Circular Saw Blade, Efficut T.C.T, 260



Other

[User manual](#)

[Parts drawing](#)